




TOTAL RECALL

Rack & Desktop



Number of Channels:

4, 8, 12, 16, 20 or 24 (Total Recall Desktop)
 4, 8, 12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52,
 56, 60, 64, 68 or 72 (Total Recall Rack)
 Available in multiples of 4, 8 or 12 channel DSP
 cards
 Channel upgrade options available

Security:

Password required
 Two levels: Administrator and User

Coding Method:

8kbps High Quality Vector Quantisation

Frequency Response:

300 > 3,400 Hz, +/- 0.5dB

Record (PIP) Tone:

1.4kHz. Channel and Level selectable
 (-21dB to -33dB)

Recording Triggers:

VOX (noise) or Off-Hook (voltage) detection:

VOX 6	-20 dB	Off-Hook 6	30 V
VOX 5	-24 dB	Off-Hook 5	25 V
VOX 4	-28 dB	Off-Hook 4	20 V
VOX 3	-32 dB	Off-Hook 3	15 V
VOX 2	-36 dB	Off-Hook 2	10 V
VOX 1	-40 dB	Off-Hook 1	5 V

Internal Storage:

SATA Hard Disk Drive providing storage for
 60,000 hours / 350,000 records onboard.

Archive Device:

Built-in Sony DVD/CD archive drive standard on Desktop and Rack

Blu-Ray archive drive optional on Desktop and Rack

Optional TCP/IP Network Archiving Support on Rack

Archive Media

CD-R - approx 180 hours per disc

DVD+RW - approx 1000 hours per disc

Blu-Ray (*Optional on Desktop and Rack*) – approx 6000 hours per disc

TCP/IP Network Archive (*Optional on Rack*) – Dependant on capacity at storage destination. 250,000 records per archive

Display:

135 mm x 100 mm Colour TFT backlit LCD

Power Requirements: 90VAC - 260VAC, 50Hz > 75Hz. 50 watts maximum

Analogue Ports:

8, 12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 68, or 72

RJ11C/RJ12/RJ14 (PSTN) line interface ports.

DSP interface uses pins 3/4 and 2/5

Line Out Jack (3.5mm stereo phono)

Headphone Jack (3.5mm stereo phono)

Modem Interface:

DB9 male connector, serial line interface, RS-232 57Kbps, Hardware Handshake. (Modem not supplied)

Network Interface:

RJ45 connector, internal 10/100mbs embedded network adapter

Client Software:

Total Recall Remote Manager, compatible with Windows 2000/ME/XP/Vista32/Vista64/7

System Software:

Field upgradeable via CD Media

Operating System:

Linux (CentOS 5.2)

Desktop Enclosure:

UL 94V-0 ABS plastic.

Desktop Unit Size:

175H x 370W x 365D mm.

6¾"H x 14½"W x 14¼"D

Desktop Unit Weight:

6 kg net

13 lb net.

Rack Mount Enclosure:

Zinc Passivated steel with Powder-Coated face panel.

Standard EIA 19" Rack configuration (5U).

Rack Mount Size:

220H x 480W x 230D mm (5U)

8½"H x 19"W x 9"D

Rack Mount Weight:

10 kg net

22 lb net

Specifications subject to change without notice.

For more information visit TOTAL RECALL on the Web at www.totalrecallvr.com
All the trademarks are property of their respective owners.

Copyright © 2009 Comsec TR Pty Ltd. All rights reserved. The information in this publication is subject to change without notice. Comsec TR Pty Ltd assumes no responsibility for any errors that may appear in this publication.

In Australia:
Comsec TR Pty Ltd
5/ 7 Millennium Court
Silverwater NSW 2128
Australia
Tel: +61 2 9748 2304
sales@totalrecallvr.com

