




# TOTAL RECALL MAX

## Desktop



When your business depends on  
**CALL RECORDING**  
YOU NEED TOTAL RECALL MAX



### Benefits

- ☑ **Affordable** – best cost per channel ratio without compromise on features.
- ☑ **Reliable** – stable operating platform with built-in redundancy.
- ☑ **Secure** – tamper proof recording format and role based access control.
- ☑ **Hybrid** – records VoIP and/or ISDN calls.
- ☑ **Accessible** – remote access and control software included.
- ☑ **Powerful** – comprehensive recording, search, monitoring and playback capability.
- ☑ **Flexible** – single license key for different channel types, in any combination.

### Key Features

- ☑ SIP and ISDN call recording.
- ☑ Wide range of recording options.
- ☑ Standalone or part of a network.
- ☑ 60,000 channel hours recording capacity
- ☑ Secure and tamper proof recording format.
- ☑ Advanced audio compression.
- ☑ One-click real-time call monitoring.
- ☑ Feature rich player.
- ☑ Comprehensive search capability.
- ☑ Network & DVD/CD archiving.
- ☑ Stable UNIX platform.
- ☑ Remote access and management software.

## Telephony

- SIP (RFC3261, RFC2976, RFC2833), SDP (RFC3264), RTP (RFC 3550)
- ISDN PRI (ITU-T Q.931, National ISDN 1 & 2, Nortel DMS 100, AT&T 4ESS, Lucent 5ESS, Euro ISDN)

## Voice Processing

- PCM (ITU-T G.711a and G.711mu law)
- SPEEX (3:1)
- WAV (16 bit, 8KHz) & MP3 export

## Channel Capacity

- 60 simultaneous SIP sessions
- 60 simultaneous ISDN calls
- Up to 60 SIP sessions and/or ISDN calls in any combination in hybrid mode

## Storage Media

- Internal mirrored 250 GB SATA hard drive storage. Up to 60,000 channel hours, maximum 350,000 individual records.

## Recording Trigger

- ISDN D channel
- VoIP SIP session

## Monitoring

- Real-time continuous monitoring via Remote Manager software

## Replay

- Replay via Remote Manager software
- Start, stop, fast-forward, rewind and pause control

## Archive Media

- CD-R (aprox 180 hours per CD), DVD+RW (aprox 1000 hours per DVD)
- Network Attached Storage: NFS v2/3, CIFS/SMB (250,000 records per archive, up to maximum hard disk capacity)

## Client Software

- Total Recall Max Remote Manager for Windows 2000/XP/Vista

## Networking

- Two 100/1000Mb Ethernet ports
- Single RS232 port (for modem connection)
- Network time synchronization via NTP
- Alarms via SNMP
- TCP/IP CDR interface (optional)

## System

- Dimensions: 160(H) x 420(W) x 420(D) mm
- Weight: 10Kg
- Single auto-sensing 300W PSU
- 0°C - 60°C operating temperature
- 0°C - 60°C storage temperature
- 5% - 90% non-condensing humidity

---

For more information visit TOTAL RECALL on the Web at [www.totalrecallvr.com](http://www.totalrecallvr.com)

All the trademarks are property of their respective owners.

Copyright © 2008 Comsec TR Pty Ltd. All rights reserved. The information in this publication is subject to change without notice. Comsec TR Pty Ltd assumes no responsibility for any errors that may appear in this publication.

### **In Australia:**

*Comsec TR Pty Ltd  
5/7 Millennium Court  
Silverwater NSW 2128  
Australia*

**Tel: +61 2 9748 2304**  
[info@totalrecallvr.com](mailto:info@totalrecallvr.com)

