



# TOTAL RECALL MAX

## *Rack*



When your business depends on  
**CALL RECORDING**  
YOU NEED TOTAL RECALL MAX



### Benefits

- ☑ **Affordable** – best cost per channel ratio without compromise on features.
- ☑ **Reliable** – stable operating platform with built-in redundancy.
- ☑ **Secure** – tamper proof recording format and multi-level access control.
- ☑ **Hybrid** – records from Analog, VoIP and/or ISDN interfaces.
- ☑ **Accessible** – remote access and control software included.
- ☑ **Powerful** – comprehensive recording, search, monitoring and playback capability.
- ☑ **Flexible** – single license key for different channel types, in any combination.

### Key Features

- ☑ SIP, ISDN and Analog call recording.
- ☑ Broadcast audio recording.
- ☑ Standalone or part of a network.
- ☑ Wide range of recording options.
- ☑ 60,000 channel hours recording capacity.
- ☑ Secure and tamper proof recording format.
- ☑ Advanced audio compression.
- ☑ One-click real-time call monitoring.
- ☑ Feature rich player.
- ☑ Comprehensive search capability.
- ☑ Network & DVD/CD archiving.
- ☑ Stable UNIX platform.
- ☑ Remote access and management software.

## Telephony

- SIP (RFC3261, RFC2976, RFC2833), SDP (RFC3264), RTP (RFC 3550)
- ISDN PRI (ITU-T Q.931, National ISDN 1 & 2, Nortel DMS 100, AT&T 4ESS, Lucent 5ESS, Euro ISDN)
- Analog 2-wire POTS, FSKR, DTMF

## Voice Processing

- PCM (ITU-T G.711a and G.711mu law)
- SPEEX (3:1) & HQVQ (8:1) compression
- WAV (16 bit, 8KHz) & MP3 export

## Channel Capacity

- 60 simultaneous SIP sessions
- 60 simultaneous ISDN calls
- 32 simultaneous Analog calls
- Up to 60 SIP sessions and/or ISDN calls in any combination, plus 32 analog channels.

## Storage Capacity

- Mirrored, swappable 250GB SATA hard drive storage up to 60,000 channel hours at 16 kbps HQVQ compression. Maximum 350,000 individual calls.

## Recording Trigger

- 24 hour continuous
- On-demand (via software or DTMF sequence)
- Off-Hook
- VOX (6 different levels)
- ISDN D channel
- VoIP SIP session

## Monitoring

- Real-time monitoring via on-board speaker
- Real-time monitoring via Remote Manager software

## Replay

- Replay via on-board speaker
- Replay via Remote Manager software
- Start, stop, fast-forward, rewind and pause control

## Archive Media

- CD-R (aprox 180 hours per CD), DVD+RW (aprox 1000 hours per DVD)
- Network Attached Storage: NFS v2/3, CIFS/SMB (250,000 records per archive, up to maximum hard disk capacity)

## Client Software

- Total Recall Max Remote Manager for Windows 2000/XP/Vista

## Networking

- Two 100/1000Mb Ethernet ports
- Single RS232 port (for modem connection)
- Network time synchronization via NTP
- Alarms via SNMP
- TCP/IP CDR interface (optional)

## System

- Dimensions:220(H) x 450(W) x 420(D) mm (5 RU)
- Weight: 20Kg
- Hot-swap auto-sensing 320+320W PSU

---

For more information visit TOTAL RECALL MAX on the Web at [www.totalrecallvr.com](http://www.totalrecallvr.com)

All the trademarks are property of their respective owners.

Copyright © 2008 Comsec TR Pty Ltd. All rights reserved. The information in this publication is subject to change without notice. Comsec TR Pty Ltd assumes no responsibility for any errors that may appear in this publication.

**In Australia:**

*Comsec TR Pty Ltd  
5/7 Millennium Court  
Silverwater NSW 2128  
Australia*

**Tel: +61 2 9748 2304**

**[info@totalrecallvr.com](mailto:info@totalrecallvr.com)**

