



TOTAL RECALL

Rack



When your business depends on
CALL RECORDING
 YOU NEED TOTAL RECALL



Benefits

- ☑ **Affordable** – best cost per channel ratio without compromise on features.
- ☑ **Reliable** – stable operating platform with built-in redundancy.
- ☑ **Secure** – tamper proof recording format and role based access control.
- ☑ **Accessible** – remote access and control software included.
- ☑ **Powerful** – comprehensive recording, search, monitoring and playback capability.

Key Features

- ☑ Analog call recording.
- ☑ VoIP call recording.
- ☑ Standalone or part of a network.
- ☑ Onboard storage for 60,000 hours / 350,000 calls.
- ☑ Secure and tamper proof recording format.
- ☑ Advanced audio compression.
- ☑ One-click real-time call monitoring.
- ☑ Comprehensive search capability.
- ☑ Easy to use DVD/CD archiving.
- ☑ Optional Blu-Ray and TCP/IP Network archiving.
- ☑ Stable UNIX platform.
- ☑ Remote access and management software.

Telephony

- Analog 2-wire POTS, FSKR, DTMF
- SIP (RFC3261, RFC2976, RFC2833), H.323 (ITU-T H.323, ITU-T H.225, ITU-T H.245), SDP (RFC3264), RTP (RFC 3550)

Voice Processing

- PCM (ITU-T G.711a and G.711mu law)
- SPEEX (3:1) & HQVQ (8:1) compression
- WAV (16 bit, 8KHz) & MP3 export

Channel Capacity

- 72 simultaneous Analog recording channels
- 8 simultaneous VoIP recording channels
- 8 simultaneous VoIP recording channels, combined with 8 Analog recording channels

Storage Capacity

- Internal SATA hard drive storage for up to 60,000 hours / 350,000 calls at 16 kbps HQVQ compression.

Recording Trigger

- On-demand (via software or DTMF sequence)
- Off-Hook (6 different levels)
- VOX (6 different levels)

Monitoring

- Real-time monitoring via on-board speaker
- Real-time monitoring via Remote Manager software

Replay

- Replay via on-board speaker
- Replay via Remote Manager software
- Start, stop, fast-forward, rewind and pause control

- Single press 'Quick Replay' function to review recent calls.

Archive Media

- CD-R (aprox 180 hours per CD), DVD+RW (aprox 1000 hours per DVD)
- Optional TCP/IP Network archiving support (250,000 records per archive, up to maximum hard disk capacity)
- Optional Blu-Ray archive device (aprox 6000 hours per BD-RE)

Client Software

- Total Recall Remote Manager for Windows 2000/XP/Vista32/Vista64/7

Networking

- One 100Mb Ethernet port
- Single RS232 port (for modem connection)
- Network time synchronization via NTP
- Optional alarming via SNMP
- Optional TCP/IP SMDR interface

System

- Dimensions: 220(H) x 480(W) x 230(D) mm (5 RU)
- Weight: 10Kg
- Single auto-sensing 180W PSU
- Optional Hot-Swap 350+350W PSU
- Max power draw 80W

For more information visit TOTAL RECALL on the Web at www.totalrecallvr.com

All the trademarks are property of their respective owners.

Copyright © 2011 Comsec TR Pty Ltd. All rights reserved. The information in this publication is subject to change without notice. Comsec TR Pty Ltd assumes no responsibility for any errors that may appear in this publication.

In Australia:

Comsec TR Pty Ltd
5/7 Millennium Court
Silverwater NSW 2128
Australia

Tel: +61 2 9748 2304
sales@totalrecallvr.com

