

TotalRecallVR LinX Essence

Compact stand-alone appliance for medium capacity IP audio logging and call recording in an incredibly small package.

- ✓ 60 IP recording channels
- ✓ 60,000 audio hours recording storage at 64Kbps
- ✓ 600,000 recordings DB storage
- ✓ 3 activation licenses for PC applications
- ✓ 2 years warranty



- ✓ Reliable
- ✓ Affordable
- ✓ Secure
- ✓ Hybrid

Easily and securely record:

Telephones

Record IP (or VoIP) telephones using SIP, SIPrec and Cisco® Built in Bridge (BiB).

2-way Radio

Record 2-way radios and consoles using RoIP, Omnitronics® RoIP, Tait® VRP and Hytera® HDAP.

Intercoms

Record IP intercoms and emergency help points using AoIP, SIP and SIPrec.

Broadcast Radio

Record public broadcast radio using AoIP, RoIP and RTSP.

Public Address

Record IP public address and announcement systems using AoIP, SIP, SIPrec and RTSP.

Air Traffic Control

Records IP (or VoIP) air traffic management (ATM) and control (ATC) systems using ED-137.



TotalRecallVR LinX Essence


- ✓ 60 IP recording channels
- ✓ 60,000 audio hours recording storage at 64Kbps
- ✓ 600,000 recordings DB storage
- ✓ 3 activation licenses for PC applications
- ✓ 2 years warranty (3, 4 or 5 years optional)
- ✓ Complementary firmware upgrades
- ✓ Complementary support

- ✓ Reliable Intel® & Linux® based platform
- ✓ Tamper proof file format
- ✓ Export to .mp3, .wav, .spx, .afic, .au ...
- ✓ Monitor, replay, reconstruct, search ...
- ✓ Choice of 10 value-add PC applications
- ✓ Multi-level access control
- ✓ APIs: REST, Java RMI, SIP, RTSP ...
- ✓ On-board network and USB archiving
- ✓ NTP clock, SNMP alarms, SMDR integration

- ✓ Tiny-box form factor: 180 x 126 x 68mm
- ✓ Powder coated steel
- ✓ 10.1" colour LCD screen with integrated speaker
- ✓ Custom 24 key keyboard
- ✓ Fan-less design
- ✓ 2 x gigabit network interfaces
- ✓ 0°C to 45°C operating temperature
- ✓ 12VDC power supply


- ✓ Solid state disk (SSD) option
- ✓ AMBE decoder option
- ✓ 2x audio storage option
- ✓ BluRay/DVD/CD disc archiving option

TotalRecallVR LinX Essence




✓ IP Recording Interface

- Capacity: up to 60 concurrent sessions
- Interface: Ethernet, 2 x 1GBps, RJ45
- Protocols: SIP, SDP, RTP, SIPrec, Cisco® BiB, RTSP, ED-137, Tait® VRP, Hytera® HDAP, Omnitronics® RoIP
- Voice encoding:
 - G.711, 8000Hz, 64Kbps, mono
 - AMBE, 8000Hz, 2450bps, mono
 - PCM, 8000Hz, 128Kbps, mono
- Passive packet capture: via SPAN port
- Active packet capture: TCP, unicast & multicast UDP



TotalRecallVR LinX Essence



All Australian design,
development and
manufacturing.

Equally popular with
enterprises,
governments, utilities,
infrastructure, militaries
... world wide.

trvr@prolancer.com.au

+61 2 8060 3311



Total Recall VR is designed, developed and manufactured in Australia by Prolancer Pty Ltd,
2/34a Olive Street, Kingsgrove NSW 2208, Australia.

www.TotalRecallVR.com